

SPX100

AC and DC System Power Supply for 19" system rack

Introduction

The SPX100 System Power Supplies are part of the arcutronix Multi Service Platform and designed for installation into arcutronix 19" system rack SRX.

Each system rack has 2 slots for redundant power supply. It can be equipped with AC or DC power supplies to fit into typical telecom as well as in other application scenarios. Redundancy (AC + AC, DC + DC or AC + DC) gives security and carrier class availability.

All arcutronix rack mount cards inside the 19" system rack are supplied via rack backplane and system rack power management.

The intelligent SRX power management is a power share bus indicating the available power left to feed the rack mount cards. This allows protecting running services and an effective utilization of the power supply capabilities.



Specifications

Features

- Redundancy-capable (int)
- Hot swappable
- Single voltage: 5 VDC, 20 A
- Mains supply: -48 V DC or 115/230 V DC
- 8HP panel
- 3RU rack mount card

Electrical

- SPX100-AC:
 - Supply voltage: 110/240 VAC, 100 VA
 - Frequency: 50 Hz
 - Supply current: < 2.0 A
 - Inrush current: < 10 A
 - Output: 5 VDC / 20 A
 - Fuse, type: T2.5A; 250V
- SPX100-DC:
 - Supply voltage: 48...72 V DC, 100 W
 - Supply current: < 3.5 A
 - Inrush current: < 10 A
 - Output: 5 VDC / 20 A
 - Fuse, type: 4 A T

Environmental

- Operating: +5 to +40°C
- Storage: -30 to +80°C
- Humidity: 10 to 90%, non-condensing

Physical

- Dimensions:
 - Height: 133,35 mm (3RU)
 - Width: 40,64 mm (8 HP)
 - Depth: 390,00 mm
- Weight: 0,6 kg

Specification may change without prior notice. Please refer to www.arcutronix.com for latest data-sheets.

For more information please contact arcutronix GmbH or visit us at www.arcutronix.com.

Version 03/11 © 2011 arcutronix GmbH